

7. WOOD SCREEN

<u>KEY</u>

[HB] Hose Bib [DS] Down Spout

----Property Line

Please note : This landscape design, accompanying project notes and resources are for layout and illustration purposes only. In no way are they to be interpreted as construction. All dimensions are approximate and must be field-verified. Refer to agreement between client and contractor for actual approved scope of work and further information. Actual construction appearance, materials, quantities and sizes may vary from that shown on plan.

8. RAISED BED

HARDSCAPE PLAN Scale: 1/4" = 1'-0"

14. DRIP IRRIGATION - Install drip irrigation for 2 zones from the Hose Bib. Use Orbit 2 Outlet Programmable Hose Faucet Timer and Rain Bird Landscape Drip products. Provide drip irrigation to all planters shown on plan.

All grading should ensure positive drainage throughout the whole project. All paved areas and all planter beds should slope to drain at a minimum rate of 2% away from the house. Install sleeves as needed, for future irrigation and lighting. Final construction means and methods to be determined by the Contractor. 1. PAVER PATIO, 14' x 16' and approx. 240 SF - sandset installation with no gaps in between, on a compacted Product - Sandstone HydraPressed Slabs from Abbotsford Concrete Products, 2. <u>PAVER PATH</u>, approx. 250 SF - sandset installation with 2" gap in between on a compacted base of 5/8" minus crushed gravel and paver sand. Install Mexican Beach pebbles in the gap between the pavers. Product - Sandstone HydraPressed Slabs from Abbotsford Concrete Products, Product - Mexican Beach Pebbles, Size - 1" - 2" Color - Black, unpolished 3. EDGING, approx. 165' - install Snap Edge Paver Restraint edging to secure paver, pebble and gravel materials in the hardscape areas, seperate from planting beds. 4. <u>RETAINING WALL</u>, approx. 65 LF - build a 6" high wall / border to hold the crushed gravel base for the rubber Product - Manorstone retaining wall block from Mutual Materials Size - 6"x16"x12" flat face, straight side Color - Natural 5. PLAY AREA, approx. 300 SF - Install a 3"-4" compacted sub-surface base of 5/8" minus crushed gravel. Install the rubber tile mats using the connector pins in between the tiles. Refer to product documentation.for further details. Product - Eco-Safety 2.5-inch Rubber Playground Surfacing Tiles Size - 20" x 20" Thickness: 2.5" Color - Terra cotta. 6. CUSTOM SWING SET - Contractor to build the framework of the swing set. Refer to Sheet 3-Details page (3.1) for recommendations on the dimensions and the specifications. Client to purchase and install swings customized to their needs. Client to install optimum chain lengths that meets the maximum 7' clearnace for the swings. 7. WOOD SCREEN - Contractor to build a cedar wood screen to hide the generator unit. Refer to the Sheet 3-Details page (D3) for recommendations on the dimensions and the specifications. Each of the 3 screens will be attached to the posts with latches, so that the screens maybe removed for servicing of the generator. 8. RAISED BED w/ WOOD SCREEN - Contractor to build a raised bed to match the layout in the plan. Attach a cedar wood screen to hide the A/C unit as located in the plan. Refer to the Sheet 3-Details page (3.2) for recommendations on the dimensions and the specifications. Refer to the Sheet 3-Details page (3.3) for wood 9. CRUSHED GRAVEL AREAS - Install 5/8" minus crushed gravel in the areas marked on the plan. Use a dirt tamper / plate compactor to pack and level the gravel. 10. ALL PLANTING BEDS - Amend all planting beds with 3" of compost and bio-char. Rototill, if necessary, esp. in compacted areas. After planting, mulch with Pro Mulch (a mix of compost and aged forest products) from Cedar 11. OUTDOOR BLACKBOARD - Client to build a custom blackboard similar to the one shown in the image below. * Use Dunn Lumber's 4'x8' ACX Plywood (A side is smooth, C side is rough and X denotes exterior glue). * Apply two coats of exterior primer on both sides of the plywood. Dry between coats and then let it dry for 24-48 hours. * Apply two coats of chalkboard exterior paint on A side. Dry between coats and then let it dry for 24-48 hours.

* Optional - frame the blackboard with a 2" cedar wood frame and paint it to match the play area rubber tiles.

12. <u>DECORATIVE PANEL</u> - To improve the view from the Sunroom window looking towards fence, install a decorative panel on the fence. Here are a few ideas for inspiration -



Modinex Composite Panel

4' x 2' from Home Depot





4' x 3' from Wayfair.com

Custom Blackboard for style reference

designed & build by us for a different project

Metal Wall Art by Rustica Ornamentals sold on Etsy.com

13. <u>FURNITURE</u> - The design shows the exact dimensions and preferred layout of the furniture and firepit table picked by the Client at Summer House in Bellevue.





DATE 04-24-2017